

## GMBE-Series Stainless & Carbon Steel Multi-Bag Liquid Vessels

GMBE-Series Stainless & Carbon Steel Multi-Bag Liquid Vessels are designed to offer a high-quality and economical solution for a variety of high flow and high load applications. The V-ring tubesheet design provides a positive snap-fit to ensure against by-pass.

### Features

- 304, 316L Stainless Steel and Carbon Steel construction
- Epoxy-coated exterior (CS only)
- 150 PSI pressure rating
- RF or DIN Flanged "inline" inlet/outlet connections
- Snap-fit V-ring bag seal design
- Stainless steel perforated support baskets (9/64" perf. standard)
- Permanent compression/hold-down plate
- Heavy-duty welded angle mounting/support legs
- Easy-access eye-nut/swing-bolt closure with bearing-assisted hand-wheel davit
- Single o-ring seal (Buna-N standard)
- Mesh-lined/perforated baskets

### Options

- Mesh-lined/perforated baskets
- Alternate Seal Materials
  - EPDM (required for NSF-61)
  - Teflon® Encapsulated Viton® ★
  - Viton® ★



### Flow Rate

Model	# of Bags	Bag Size	Basket Depth	EFA (ft²)	Max Flow Rate (GPM)*
GMBE430	4	#2	30"	17.6	600
GMBE630	6	#2	30"	26.4	1200
GMBE830	8	#2	30"	35.2	1600
GMBE1230	12	#2	30"	57.8	2400

\* Is the maximum flow rate recommended through the vessel without a filter bag installed (using water). Any increase in viscosity and/or the installation of filter bags will reduce these flow rates significantly. Please refer to the appropriate bag filter sizing chart or consult with your Global Filter representative when sizing.



NSF Certification applies for use only with drinking water. Only products bearing the NSF Mark on the product, product packaging, and/or documentation shipped with the product are Certified. Product options denoted with asterisk (★) are not included in the Certification.

### Ordering Information

GMBE	# of Bags/ Baskets	Basket Depth	Inlet/Outlet Size	Inlet/Outlet Style	Material	Pressure Rating	Surface Finish	NSF
	4	30 = 30"	4 = 4" / DIN100	D = DIN Flange	4 = 304SS	15 = 150 PSI @ 250°F	EC = Epoxy Coated (CS Only)	Blank = None
	6		6 = 6" / DIN150	F = RF Flange	6 = 316SS		GB = Glass Bead (SS Only)	MC = NSF-61
	8		8 = 8" / DIN200		C = Carbon Steel ★			
	12							

DISCLAIMER: Filtration data presented is representative of performance observed in controlled laboratory testing. It is not given as a warranty, specification or statement of fitness for use. Specific performance can vary widely depending on contaminant type, fluid properties, flow rates and environmental conditions. It is recommended that users conduct thorough qualification testing to assure the product functions as required.

SV\_GMBE\_0524